

LAYFLAT HOSE AND FITTINGS

For all your fluid pumping needs

SALUMA'S LAYFLAT HOSE IS DURABLE AND LONG-LASTING

It's highly resistant to common chemicals and has excellent resistance to UV radiation, hydrolysis and fungus degradation. The abrasion resistance is one of the highest available, making it ideal for mines and other challenging environments.



8", 10" and 12" diameters available



200 metre lengths



Reel sold separately.
Custom colours and logos available



- ABRASION: 4000 DIN CYCLES
- TEMPERATURE RANGE: -50C TO 80C (-58F TO 176F)
- COMES WITH TEMPORARY SHIPPING REEL (NOT SHOWN)

Layflat hose and fittings

Saluma's layflat hose is reinforced with circular woven filament polyester yarn. This method gives a strong bond between the cover and the lining and firmly encapsulates the woven polyester.

8"

LAYFLAT HOSE	
inches	8"
mm	204
TOLERANCE	204-207
WALL THICKNESS	
inches	0.150 ± 0.012
mm	3.8 ± 0.3
WORKING PRESSURE	200
BURSTING PRESSURE	600
WEIGHT	
lbs/ft	1.94
tolerance lbs/ft	± 0.134
kgs/m	2.90
tolerance kgs/m	± 0.2
ELONGATION AT WP (%)	
max	≤ 1
EXPANSION AT WP (%)	
max	≤ 10
PART#	217130

10"

LAYFLAT HOSE	
inches	10"
mm	254
TOLERANCE	256-259
WALL THICKNESS	
inches	0.165 ± 0.016
mm	4.2 ± 0.4
WORKING PRESSURE	200
BURSTING PRESSURE	600
WEIGHT	
lbs/ft	2.75
tolerance lbs/ft	± 0.201
kgs/m	4.10
tolerance kgs/m	± 0.2
ELONGATION AT WP (%)	
max	≤ 1
EXPANSION AT WP (%)	
max	≤ 10
PART#	217140

12"

LAYFLAT HOSE	
inches	12"
mm	306
TOLERANCE	306-311
WALL THICKNESS	
inches	0.165 ± 0.016
mm	4.2 ± 0.4
WORKING PRESSURE	150
BURSTING PRESSURE	450
WEIGHT	
lbs/ft	3.33
tolerance lbs/ft	± 0.201
kgs/m	4.97
tolerance kgs/m	± 0.3
ELONGATION AT WP (%)	
max	≤ 1
EXPANSION AT WP (%)	
max	≤ 8
PART#	217150



Hose optional equipment:

- Layflat Hose Spool - Powder Coated
- Layflat Spool Skid - Holds 2 Spools
- Hydraulic Spooling System - Painted